

Proprietary Note: W.L.Gore & Associates, Inc. Proprietary Data; The data and information disclosed hereon is furnished upon the following understanding and agreement: By acceptance of this document you agree that all rights to the drawings, specifications, processes, and other data contained therein, as well as the proprietary and novel features of the subject matter are reserved by W.L.Gore and disclosed in confidence. They are not to be disclosed to others unless and until expressly authorized by W.L.Gore & Associates Inc.

A4

Falls nicht anders definiert, alle Maße in mm.
Unless otherwise specified all dimensions in mm.

Maße ohne Toleranzangabe sind Nominalmaße.
All dimensions nominal unless otherwise specified.

Schematische Darstellung
Schematic view only

Maßstab/Scale

Toleranzen/Tolerances

./.

./.

Benennung/Description

COAXIAL CABLE



W.L.Gore & Associates GmbH
Nordring 1
91785 Pleinfeld
Tel. 0 91 44 / 60 10
Fax 0 91 44 / 63 61, 68 16

Zeichnungsnr./Drawing no.

GSC-03-40966-00

Blatt/Page

1/2

Ersatz für / Replacement for

Ersetzt durch / Replaced by


Revision	Datum/Date	Gezeichnet/Drawn	PLFECO no.
A	15.04.11	SH	4836

Construction

1. Conductor		material	tinned copper
		size	AWG 22 (154/44)
2. Insulation		material	HSTF tape
		colour	white
3. Served wire shield		material	tinned copper
		size	AWG 40 (01)
4. Binder		material	ePTFE
5. Jacket		material	polyurethane
		colour	black

Characteristics

Capacitance	575 pF/m max.
Impedance	10 ±2 Ω
Inductance	130 nH/m max.
Current load	3A max.
Operating temperature range	-40°C to +90°C

Ersatz für / Replacement for		Ersetzt durch / Replaced by		Formular Beschreibung / Description	
				Coaxial Cable	
A	15.04.11	SH	4836		
Revision	Date	Author	PLFECO no.		
 W.L. Gore & Associates GmbH Nordring 1 D-91785 Pleinfeld				Tel 09144 / 601-0 Fax 09144 / 6361, 6816	
				Identnr. / Ident No. GSC-03-40966-00	
				Seite / Page 2/2	